

LOOK SOLUTIONS COBRA 3.1

www.lbtpro.com / info@lbtpro.com

- 3100W
- Vaporizing Fog Generator
- 5 Liter Capacity
- 100 Steps
- 100% output approx. 55 sec.



Specifications

Procedure	Vaporizing fog generator
Power requirement	3100 Watt or 1800 Watt
Voltage	230 V/50 Hz or 120 V/60 Hz
Heat-up time	approx. 15 min. / 20 min.
Fluid consumption, measured with Look Regular-Fog at max. Output	260 ml/min. / 175 ml/min.
at continuous output	46 ml/min. / 28 ml/min.
Fluid tank capacity	5 Liter
Fog output	adjustable in 100 steps of 1%
Output projection	max. 25 m
Fogging time at 100% output	Extended-Mode: approx. 55 sec. / 50 sec. Impulse-Mode: approx. 22 sec. / 22 sec.
at < 30% output	Continuous output
Control	Manual 0 - 10 V analogue DMX 512 Ethernet (Artnet, sACN) Timer Radio remote (option) XLR-remote (option)
Temperature control	Microprocessor controlled
Overheating protection	Heater block/Thermostat Pump/Thermal switch
Dimensions (LxWxH)	58x26.5x26 cms
Weight without tank	16 kg

Advantages

- Extremely silent nozzle
- Two pumps for strong, constant output
- Control via Ethernet, DMX 512, analogue (0 - 10 V) and manual mode
- Internal Timer
- Adjustments via Touchscreen with simple menu
- Several RDM features
- Fog output adjustable from 0 - 100% in steps of 1%
- Adjustable Pump characteristic
- Working hours counter
- Production and Service in Germany

Accessories (Option)

- XLR-remote for analogue control
- Radio remote

Dimensions

