

MOVING STROBE 800

www.lbtpro.com / info@lbtpro.com

- 80 Degree Beam
- 96 pcs 5W White LED
- 972 pcs 0.4W RGB LED



M STROBE 800 has 96pcs high brightness 5W white SMD led for main white light output, and subsidiary lighting is used 972pcs 0.4W RGB leds. Supporting pixel control, key light(W) has 6 segments which can be individually controlled, and RGB has 12 pixel control function. It is a more powerful strobe light using white leds, around 450W output on continuous lighting mode, whole fixture has around 800W output on flashing mode.

Optics System

Light source: 96pcs 5W white led & 972pcs RGB leds
Beam Angle: 80 degree



Electric

Input Power: 800W

Electronic Control Technology

Protocol: DMX512

Control Mode: DMX512, Auto run, Master and Slave

DMX Channel: 11/12/13/17/20/27/44/46CH

Control Panel: OLED touch Display

Strobe Speed: 1-25 times/second

Dimmer: 0-100% linear dimming

Construction

Package Dimension: 535*280*420cm (1pcs)

Net Weight: 12kg (unit package)

Shell Color: Black

Signal Connection: 3-pin/5-pin DMX in/out

IP rating: IP20

Installment

Position: 0-180 degree

Hanging: standard hanging

Safety: Safety cable

Working Tem.: -10-40 degree

Standard Spare Parts List

Cable: 1pcs power cable with plug

User Manual: 1pcs english version user manual

