

S-PLAY MINI

- www.lbtpro.com / info@lbtpro.com
- DMX in/out
 - Ethernet Port
 - Reset/Trigger Button
 - Forward-facing LED



ENTTEC



DIN-rail-mountable DMX recorder + smart light show controller.

ENTTEC's S-PLAY MINI is a robust and compact show recorder and playback controller that streamlines your light show by seamlessly integrating external hardware, enabling you to achieve professional lighting control with ease.

S-PLAY MINI generates a maximum of 16 light Static/Dynamic/Effect Cues by recording two Universes of Art-Net/sACN sources or one complete Universe via DMX port live recording. Alternatively, you have the option to use the onboard pixel effects generator – an easy-to-use tool for creating gradient Effect Cues in just a matter of minutes.

The S-PLAY MINI gives you the ability to fully integrate external devices into your installation – and not just light fixtures. Receive triggers from buttons, switches or sensors to automate 3rd party devices or machinery using contact closures, Art-Net, sACN, DMX, UDP or OSC.

Using the S-PLAY MINI's handy web browser interface, simply drag and drop within the timeline to design up to eight playlists using created Cues, Events and Triggers as building blocks. Control the priority, fade times, number of play counts, and master intensities to tweak your playlists.

Play back your program on power up with preset loop times, or choose to trigger the playlists with a custom interface or external triggers in a different fashion to play back up to eight playlists simultaneously overlapping and blending with each other, with different groups and priorities.

Technical specifications

Hardware

- Input voltage 12V DC to 24V DC
- Power input 2-pin Phoenix screw terminal
- Max power draw 3W
- Ethernet port RJ45
- DMX port Bi-directional 1 x 3-pin Phoenix screw terminal
- Digital input 4 digital inputs + 1 GND (5-pin Phoenix screw terminal)
- Relay 1 x relay (3-pin screw terminal)
- Internal show storage capacity 1GB
- LED indicators Forward-facing LED indicator + network link/activity (integrated into RJ45 port)
- Factory reset Web interface / reset button
- Mounting Surface & TS35 DIN rail mountable (clips & screws included)
- IP rating IP20
- Environmental operating temperature 0°C to 50°C / 32°F to 122°F
- Environmental operating humidity 0 to 95% (non-condensing)
- Cooling method Convection
- Body material ABS plastic
- Unit dimensions 100.5mm x 72.25mm x 34mm
- Unit weight 0.83kg / 0.18lbs
- Shipping dimensions 160mm x 140mm x 40mm
- Shipping weight 0.16kg / 0.35lbs
- Compliance RCM (Aus/NZ), CE / WEEE (EU), UKCA (UK), FCC (USA)

Software

- DMX universe playback 1U (512 channels of USITT DMX512-A)
- Art-Net / sACN universe playback 2U (1024 channels)
- Max DMX refresh rate (FPS) 40
- Max playlist count 8
- Max cue track per playlist 2
- Max Cues (including Static, Dynamic and Effect) 16
- Max Triggers 16
- Max Events 16
- OSC API Yes

Connectivity

