









- IP65
- 100W LED
- 60° Beam Angle
- Also Available in 200W RGBW











The massive beautifully designed IP65 rated Single Blinder features high powered 100W white COB LED, a wide 60° beam angle, CRI 75, 5,000 lm, 3000k to 6500k color temperature for versions warm white, cool white or warm-cool white. Our newest technology solution using the high tech LED technology DTW (dim to warm) offers the fixture when it is dimming down, that amber shift, a dim to warm effect that you use to see in the traditional halogen effect from conventional lamp lightings. Gorgeous and highly professional! It is a IP65 fixture, suitable for outdoor events.

TECHNICAL PARAMETERS

- 1. Blinder-wash 100W COB 3000k Warm White LED IP65. CRI=75 (version 1);
- 2. Blinder-wash 100W COB 6500k Cool White LED IP65. CRI=75 (version 2):
- 3. Blinder-wash 100W COB from 3000k to 6500k warm-cool white LED IP65. CRI=75 (version 3);
- 4. Blinder-wash 100W COB UV LED IP65 (version 4);
- 5. Optional dim to warm effect in above 4 versions by adding an outer 10W amber SMD (versions 5, 6, 7, 8);
- 6. High CRI for warm white, cool white & warm-cool white. CRI=92. Designed for theather, film and television applications. AC 100 240V 50/60Hz 100W/ Output: 4,120 lm (versions 9, 10, 11);
- 7. OLED display;
- 8. Unique design, manual pan adjustment, individual control of each COB module, integrated rigging bracket, operate in any angle, 4 button control panel and LCD menu display, internal chase macros, strobe effects, variable selectable dimming curves;
- 9. AC 100 240V 50/60Hz 100W/ Output: 5,000 lm, 205 lux in @5m;
- 10. 60 degrees beam angle/ 16 Bit dimmer/1,000 Hz LED scan rate;
- 11. 5 DMX channels:
- 12. Comes 1 COB, 2 COBs or 4 COBs (4 in 1 row or 2 side by side);
- 13. Weight: 3.5 Kg (extremely compact & portable).

Also Available in RGBW 200W

